

BSF-300/L: Base Station



Features

BS/CCU Connection

Ratings / Performance

Download



Request

Rating	
Operating Humidity	30% to 90% (non-condensing)
Operating Voltage	AC100V to 240V ±10%
Weight	Approx. 7kg (15.4lbs)
Dimensions	W483 x H66.4 x D405 mm (W19 x H2.6 x D15.9 inches) (excluding protrusions)
Power Consumption	Approx.55VA (BSF-300 only)
Power supply to fiber adaptor	240W maximum (including cable loss)
Input signals	
External Genlock	BNC type, 1ch (HDTV/SDTV auto detect) HD: PS(1Vp-p) or Tri-Sync Signal(0.6Vp-p±6dB) 75ohm bridged SD: VBS(1Vp-p) or BBS 75ohm bridged
SDI Return Video Signal	75ohm Single End, BNC type 2ch (HD/SD SDI selectable)
VBS Return Video Signal	75ohm Single End, BNC type 2ch
Q-TV Signal	VBS 1Vp-p 75ohm Single End, BNC type 1ch
Intercom/Tally	
Intercom(ENG/PROD)	4-Wire, Clearcom or RTS selectable
4-Wire	0dBm 600 ohm 2ch
Clearcom	-15dBs 200 ohm 2ch
RTS	0dBs 200 ohm 2ch
PGM(Program Sound)	0dBs 600 ohm/10k ohm switchable 2ch
Tally	R/G 2ch
Output signals	
HD-SDI/SD-SDI Signal	HD-SDI(SMPTE292M) /SD-SDI(SMPTE259M), 75ohm BNC type 4ch(HD-SDI/SD-SDI selectable)
WFM Signal	Serial Digital 75ohm BNC type 1ch (HD-SDI/SD-SDI selectable)
PM Signal	Serial Digital or VBS 75ohm BNC type 1ch (HD-SDI/SD-SDI selectable)
VBS Signal	1.0Vp-p 75ohm BNC type 2ch
MIC	0dBs/+4dBs Low 2ch
Support Products	<ul style="list-style-type: none"> • broadcast/HDK-55 • broadcast/HDK-73 • broadcast/HDK-79GX • broadcast/HC-HD300