

System	RH45R(Head) + RT40RB(Tripod) + BR-6B(Mid-level spreader) + FP-2B(Large rubber feet) + RC-50(Carrying case)		
Payload	12 kg / 26.5 lb	Tilt angle	+90° / -70° (Limited to ±40° with maximum counterbalance)
Weight	6.5 kg / 14.3 lb	Pan angle	360°
Height	① H: 1710 mm W: 880 mm (※Reference)	Counterbalance	Range : 4.5kg-10.5kg / 10-23.1lb (CG100mm)
	② H: 825 mm W: 670 mm ( " )		System : Continuous
Folded length	③ L: 895 mm ( " )	Drag mode	Free plus 3STEP
Camera plate (Sliding range)	Sliding plate ±40 mm / ±1.6"	Ball diameter	ø75 mm
Plate attachment (Screw sliding range)	Type: 1/4-20UNC screw with video pin	Tripod fixation	Fixing lock knob
	52 mm / 2"	Spreader	BR-6B (Telescopic, Removable)
Spare screw	Type: 1/4-20UNC, 3/8-16UNC screws	Pan handle	PH-6B
	Equipped on the top of the head (beneath sliding plate)	Case material	Nylon, Polyester, TPE, PE, PP

**Remarks**

※Counterbalance support knob is included in RS-450RM

**■ Exterior Dimensions (mm)**

